

[Buyer's Guide]

Z-3272 Series Gun Type 2D Image Handheld Scanner

Standard Device

	PIN-OUT CONFIGURATION		
	MODULE JACK_PIN#	RS-232C	USB
	#1	RTS (TTL level)	N/C
	#2	N/C	USB_D+
	#3	N/C	USB_D-
	#4	Ground	Ground
	#5	CTS (TTL level)	N/C
	#6	RXD (TTL level)	N/C
	#7	N/C	N/C
	#8	N/C	USB 5V
#9	N/C	N/C	
#10	TXD(TTL level)	N/C	

Ordering Information

Z-3272SR (Standard Range Version)

Barcode	P/N	Model Name	Remark
	88H-27SRUB-001	Z-3272SR (U) (B)	Gun Type 2D Image Handheld Scanner, black, USB Cable
	88H-27SRUB-0S1	Z-3272SR (U) (B)	Gun Type 2D Image Handheld Scanner, black, USB Cable, Stand
	88H-27SRRP-001	Z-3272SR (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable
	88H-27SRRP-U01	Z-3272SR (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable, US adapter
	88H-27SRRP-K01	Z-3272SR (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable, UK adapter
	88H-27SRRP-E01	Z-3272SR (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable, EU adapter
	88H-27SRRP-A01	Z-3272SR (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable, AU adapter

[Buyer's Guide]

Z-3272HD (High Density Version)

Barcode	P/N	Model Name	Remark
	88H-27HDUB-001	Z-3272HD (U) (B)	Gun Type 2D Image Handheld Scanner, black, USB Cable
	88H-27HDUB-0S1	Z-3272HD (U) (B)	Gun Type 2D Image Handheld Scanner, black, USB Cable, Stand
	88H-27HDRP-001	Z-3272HD (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable
	88H-27HDRP-U01	Z-3272HD (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable, US adapter
	88H-27HDRP-K01	Z-3272HD (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable, UK adapter
	88H-27HDRP-E01	Z-3272HD (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable, EU adapter
	88H-27HDRP-A01	Z-3272HD (R) (B)	Gun Type 2D Image Handheld Scanner, black, RS232 Cable, AU adapter

Standard Cable Options




- The standard cable is gray, straight, and 2 meters (6.5 feet) in length.
- The standard cable options include RS-232 and USB.
- Special Order Requirement:
ZEBEX is capable of supplying special customized cable, given that customers provide detailed pin configurations. The minimum order quantity of a special cable is 250 pcs.

1. RS-232C Communication Cable (DTE pin out)

	PIN-OUT CONFIGURATION	
	DB-9 (F)	FUNCTION
	2	TX
	3	RX
	7	CTS
	8	RTS
	5	GND
	9	+5V Input
Item Part No.	171-10R442-200	
	171-10R443-200	


[Buyer's Guide]

2. HID USB / Virtual COM USB / OPOS USB Interface with Detachable Cable Type A

	PIN-OUT CONFIGURATION	
	USB TYPE A CONNECTOR	FUNCTION
	1.	VCC
	2.	D-
	3.	D+
4.	VSS	
Item Part No.	171-10U303-200	
	171-10U302-200	






* Additional software or special firmware may be required for activating virtual COM or JPOS USB interface.

Optional Stand Selection

	88H-27ST00-001	Stand	Stand for Z-3272 Black
---	----------------	-------	------------------------

Power Adapter

Z-3272 Series requires a minimum of 350mA at 5 VDC power and consumes power from the host machine. If the host can not supply sufficient power, ZEBEX provides adapters of the following plug types:

UK Plug	US Plug	Australian Plug	European Plug	Korean Plug
				

* The figures are for reference only. The adaptor form factor is subject to change without prior notice.